

# SECURITHERM time flow shower panel

Ref. 792313CF

Time flow thermostatic, comfort 10 lpm

## DESCRIPTION

**SECURITHERM time flow shower panel - Ref. 792313CF**

Thermostatic time flow shower panel:  
Large model satin stainless steel shower panel for wall mounted, exposed installation.  
Concealed inlet via flexibles M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold or hot water supply fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
Time flow ~30 seconds.  
Flow rate 10 lpm at 3 bar.  
M $\frac{1}{2}$ " stopcocks.  
Concealed fixings.  
Filters and non-return valves.  
Shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM time flow shower panel - Ref. 792313CF**

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| Connector           | M $\frac{1}{2}$ "                                                                   |
| Technology          | Time flow                                                                           |
| Height              | 1,220mm                                                                             |
| Depth               | 100mm                                                                               |
| Width               | 250mm                                                                               |
| Flow rate           | 10 lpm                                                                              |
| Temperature limiter | Thermostatic                                                                        |
| Finish              | Stainless steel                                                                     |
| Norms               | ACS                                                                                 |
| Warranty            |  |



## ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



Stainless steel sheath, brass controls

