TEMPOMATIC MIX 4 electronic mixer

Ref. 493500

Mains supply (recessed unit)

DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 493500

Wall-mounted electronic basin mixer, kit 2/2:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Presence detection sensor at the end of the spout optimises detection.
Chrome-plated stainless steel body L. 220mm.
Cap fixed in place by 2 concealed screws.
Stopcocks.
Wall-mounted.
Recessed inlets ½".
Top or bottom supply.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.
Order with nanny joint for recessed inlet, reference: 484012

ADVANTAGES

- Exceptional water savings: 90%
- Hygiene: no manual contact
- Integrated electronic unit
- Anti-bacterial duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 493500

Supply	230/6V mains (recessed)
Connector	1/2"
Technology	Electronic
Spout length	220mm
Flow rate	3 lpm
Norms	ACS, CE, BELGAQUA, SVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY