

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 493510

Recessed mains supply, stopcocks



### DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493510**

Wall-mounted electronic basin mixer:  
 230/6V recessed mains supply.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body L. 190mm.  
 Cap fixed in place by 2 concealed screws.  
 F3/8" stopcocks.  
 For wall-mounted cross wall installation.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronic unit



Anti-bacterial duty flush

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493510**

Supply	230/6V mains (recessed)
Connector	F3/8"
Technology	Electronic
Spout length	190mm
Flow rate	3 lpm
Norms	ACS CE SVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

