

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 493516

Integrated batteries



### DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493516**

Wall-mounted electronic basin mixer:  
 Battery-operated with integrated 123 6V Lithium batteries.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body L. 190mm.  
 Cap fixed in place by 2 concealed screws.  
 F3/8" stopcocks.  
 For cross wall installation.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 493516**

|               |                                                                                         |
|---------------|-----------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                            |
| Connector     | F3/8"                                                                                   |
| Technology    | Electronic                                                                              |
| Spout length  | 190mm                                                                                   |
| Flow rate     | 3 lpm                                                                                   |
| Norms         | ACS  |
| Warranty      |      |
| Repairability |      |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing mixer

