

TEMPOMATIC MIX 4

electronic mixer

Ref. 493516

Integrated batteries



DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 493516

Wall-mounted electronic basin mixer:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated metal body L. 190mm.

Cap fixed in place by 2 concealed screws.

F3/8" stopcocks.

For cross wall installation.

Anti-blocking security.

Side temperature control with adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing mixer

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 493516

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Spout length	190mm
Flow rate	3 lpm
Norms	ACS 
Warranty	
Repairability	

