BINOPTIC MIX electronic mixer

Ref. 388MCHLH

Mains supply



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 388MCHLH

Deck-mounted electronic basin mixer:
Independant IP65 electronic unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set at 60 seconds every 24 hours after the last use).
Optimised active infrared presence detection at the end of the spout.
Body in chrome-plated brass.
PEX flexibles with filters and M3/8" solenoid valves.
Fixings reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces niches where bacteria can develop).
Side temperature control lever with long lever and adjustable maximum temperature limiter.
Drop height: 170mm, for semi-recessed basins.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- 90% water savings
- Hygiene: no manual contact
- LED diagnostic aid
- Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 388MCHLH

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	170mm
Spout length	175mm
Flow rate	3 lpm
Norms	CE, ACS, DVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

