BINOPTIC MIX electronic mixer

Ref. 398MCHLH

Mains supply



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 398MCHLH

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexibles with filters and solenoid valves M⅜".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Side temperature control with long lever and adjustable maximum temperature limiter.
Drop height: 250mm for countertop washbasins.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- 90% water savings
- Hygiene: no manual contact
- Diagnostic LED
- Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 398MCHLH

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Norms	CE, ACS, DVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

