

# BINOPTIC MIX electronic mixer

Ref. 398MCHLH

Mains supply

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 398MCHLH**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexibles with filters and solenoid valves M $\frac{3}{8}$ ".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Drop height: 250mm for countertop washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 398MCHLH**

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 230/12V mains supply                                                                                                                                                                                                                                                                                                                            |
| Connector     | M3/8"                                                                                                                                                                                                                                                                                                                                           |
| Technology    | Electronic                                                                                                                                                                                                                                                                                                                                      |
| Drop height   | 250mm                                                                                                                                                                                                                                                                                                                                           |
| Spout length  | 185mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |



## ADVANTAGES

-  90% water savings
-  Hygiene: no manual contact
-  Diagnostic LED
-  Sleek design

