

# BINOPTIC MIX electronic mixer

Ref. 488MCHLH

Battery-operated

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 488MCHLH**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexibles with filters and solenoid valves M $\frac{3}{8}$ ".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Drop height: 170mm for semi-recessed washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 488MCHLH**

|               |                                                                                                                   |
|---------------|-------------------------------------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                                                      |
| Connector     | M3/8"                                                                                                             |
| Technology    | Electronic                                                                                                        |
| Drop height   | 170mm                                                                                                             |
| Spout length  | 175mm                                                                                                             |
| Flow rate     | 3 lpm                                                                                                             |
| Norms         |  <b>ACS</b>                    |
| Warranty      |  <b>30 YEAR WARRANTY</b>       |
| Repairability |  <b>50 YEARS REPAIRABILITY</b> |



## ADVANTAGES



Hygiene: no manual contact



90% water savings



Diagnostic LED



Sleek design

