BINOPTIC MIX electronic mixer

Ref. 498MCHLH

Battery-operated



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 498MCHLH

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

123 6V Lithium batteries.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexibles with filters and solenoid valves M%".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Side temperature control with long lever and adjustable maximum temperature limiter.

Drop height: 250mm for counter-top washbasins.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



90% water savings



Total hygiene: no manual contact



Diagnostic LED




Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 498MCHLH

Supply	6V batteries
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Norms	
Warranty	30 g



© DELABIE https://www.delabie.com