# BINOPTIC MIX electronic mixer

Ref. 498MCHLH

Battery-operated

## DESCRIPTION

**BINOPTIC MIX electronic mixer** - Ref. 498MCHLH

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
123 6V Lithium batteries.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexibles with filters and solenoid valves M⅜".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Side temperature control with long lever and adjustable maximum temperature limiter.
Drop height: 250mm for counter-top washbasins.
Suitable for people with reduced mobility.
30-year warranty.

## ADVANTAGES

- 90% water savings
- Hygiene: no manual contact
- LED diagnostic aids
- Sleek design

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer** - Ref. 498MCHLH

| | |
|---|---|
| Supply | 6V batteries |
| Connector | M3/8" |
| Technology | Electronic |
| Drop height | 250mm |
| Spout length | 185mm |
| Flow rate | 3 lpm |
| Norms | |
| Warranty | |
| Repairability | |