# BINOPTIC electronic tap

Ref. 398015

Mains



## DESCRIPTION

**BINOPTIC electronic tap** - Ref. 398015

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve M⅜".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Drop height: 250mm for countertop washbasins.
Suitable for people with reduced mobility.
30-year warranty.

## ADVANTAGES

- 90% water savings
- Hygiene: no manual contact
- LED diagnostic aids
- Sleek design

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap** - Ref. 398015

| | |
|---|---|
| Supply | 230/12V mains supply |
| Connector | M3/8" |
| Technology | Electronic |
| Drop height | 250mm |
| Spout length | 185mm |
| Flow rate | 3 lpm |
| Norms | CE, ACS |
| Warranty | 30 YEAR WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |

