

BINOPTIC electronic tap

Ref. 488015

Battery-operated

DESCRIPTION

BINOPTIC electronic tap - Ref. 488015

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
123 6V Lithium batteries.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve M $\frac{3}{8}$ ".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Drop height: 170mm for semi-recessed washbasins.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 488015

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	170mm
Spout length	175mm
Flow rate	3 lpm
Norms	ACS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY



ADVANTAGES



90% water savings



Hygiene: no manual contact



LED diagnostic aids



Sleek design

