

# BINOPTIC electronic tap

Ref. 488015

Battery-operated

## DESCRIPTION

**BINOPTIC electronic tap - Ref. 488015**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexible with filter and solenoid valve M $\frac{3}{8}$ ".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Drop height: 170mm for semi-recessed washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 488015**

|               |                                     |
|---------------|-------------------------------------|
| Supply        | 6V battery                          |
| Connector     | M3/8"                               |
| Technology    | Electronic                          |
| Drop height   | 170mm                               |
| Spout length  | 175mm                               |
| Flow rate     | 3 lpm                               |
| Norms         | <b>ACS</b>                          |
| Warranty      | <b>30</b><br>YEAR<br>WARRANTY       |
| Repairability | <b>50</b><br>YEARS<br>REPAIRABILITY |



## ADVANTAGES

-  90% water savings
-  Hygiene: no manual contact
-  LED diagnostic aids
-  Sleek design

