BINOPTIC electronic tap

Ref. 498015

Battery-operated

DESCRIPTION

BINOPTIC electronic tap - Ref. 498015

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
Battery-operated with 123 6V Lithium batteries.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve M⅜".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Drop height 250mm for countertop washbasins.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- 90% water savings
- Hygiene: no manual contact
- LED diagnostic aids
- Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 498015

Supply	6V batteries
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Norms	
Warranty	
Repairability