

SECURITHERM shower panel

Ref. 792350

Dual control thermostatic mixer




DESCRIPTION

SECURITHERM shower panel - Ref. 792350

Dual control thermostatic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Concealed inlets via flexibles, M $\frac{1}{2}$ ".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C; with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
Handset with removable flexible via rapid push-fit STOP connector and wall support supplied.
~30 second time flow valve with soft-touch operation to control fixed ROUND shower head.
Non-time flow 1/4-turn valve to control handset (wall support supplied).
Concealed fixings.
Filters and non-return valves.
Shower panel suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792350

Connector	M $\frac{1}{2}$ "
Technology	Dual control
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS  
Warranty	



ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Aluminium casing, brass mixer

