TEMPOMATIC 4 electronic tap

Ref. 443500

Recessed mains supply



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443500

Wall-mounted electronic basin tap:

230/6V recessed mains supply.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body L. 190mm.

Cap fixed in place by 2 concealed screws.

Stopcock.

Wall-mounted fixings.

Recessed inlet.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443500

Supply	230/6V mains supply (recessed)
Connector	M1/2"
Technology	Electronic
Spout length	190mm
Flow rate	3lpm
Norms	ACS (€ 👺 SVGW
Warranty	30 gg wassanty
Repairability	S O S

ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Integrated electronics



Anti-bacterial duty flush



© DELABIE https://www.delabie.com