# TEMPOMIX 3 time flow mixer

Ref. 794050

Soft-touch operation

## DESCRIPTION

**TEMPOMIX 3 time flow mixer** - Ref. 794050

Wall-mounted single control time flow basin mixer, Kit 2/2:
Soft-touch operation.
Temperature control and operation via the push-button.
Time flow pre-set at ~7 seconds, adjustable from 6 to 9 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 3 - 6 lpm.
Tamperproof, scale-resistant flow straightener.
Chrome-plated metal body L. 110mm.
Wall-mounted M½".
Top or bottom supply.
Recessed inlets.
Filters and non-return valves.
Adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.
To order with inlet reference 794012.

## ADVANTAGES

- Exceptional water savings: 85%
- Soft-touch operation
- Sleek design

## TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow mixer** - Ref. 794050

| | |
|---|---|
| Connector | M½" |
| Technology | Time flow |
| Spout length | 110mm |
| Flow rate | 3 lpm |
| Norms | ACS, DVGW, BELGAQUA, WRAS |
| Warranty | 30 YEAR WARRANTY |