

# SECURITHERM EP pressure-balancing shower mixer

Ref. 2539EPS

Wall-mounted single control mixer, sculptured lever



## DESCRIPTION

**SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS**

Wall-mounted single control mechanical shower mixer.  
Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Flow rate regulated at 9 lpm.

M $\frac{1}{2}$ " shower outlet with integrated non-return valve.

Mixer with offset standard wall connectors M $\frac{1}{2}$ " M $\frac{3}{4}$ ".

Filters and non-return valves.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, nursing homes, hospitals and clinics.

Shower mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## ADVANTAGES



HW flow rate reduced if CW fails



Pressure-balancing: limits temperature variations








Ergonomic: sculptured lever is easy to grip



Water savings: flow rate regulated at 9 lpm

## TECHNICAL CHARACTERISTICS

**SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS**

Connector	M1/2"
Technology	SECURITHERM EP mechanical mixer
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	
Repairability	