SECURITHERM EP pressure-balancing shower mixer

Ref. 2539EPS

Wall-mounted single control mixer, sculptured lever



DESCRIPTION

SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS

Wall-mounted single control mechanical shower mixer.
Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
Stable temperature regardless of pressure and flow rate variations in the system.
Flow rate regulated at 9 lpm.
M½" shower outlet with integrated non-return valve.
Mixer with offset standard wall connectors M½" M¾".
Filters and non-return valves.
Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, nursing homes, hospitals and clinics.
Shower mixer suitable or people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- HW flow rate reduced if CW fails
- Pressure-balancing: limits temperature variations
- Ergonomic: sculptured lever is easy to grip
- Water savings: flow rate regulated at 9 lpm

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS

Connector	M1/2"
Technology	SECURITHERM EP mechanical mixer
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS, BELGAQUA
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

