Auto-draining shower kit with EP mechanical mixer

Ref. 2539EPSHYG

Pressure-balancing mixer

DESCRIPTION

Auto-draining shower kit with EP mechanical mixer - Ref. 2539EPSHYG

Shower kit with single control mechanical mixer.
SECURITHERM shower kit with auto-draining device.
• Mixer with Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
Constant temperature regardless of pressure and flow rate variations.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and sculptured control lever.
M½" shower outlet with integrated non-return valve.
Mixer with 2 offset standard wall connectors M1/2" M3/4".
Filters and non-return valves.
• Chrome-plated sliding shower head (ref. 813) with flexible hose (ref. 834T3) and chrome-plated, wall-mounted tilting support (ref. 845).
• Anti-stagnation device FM½" for installation between lower outlet and shower hose, automatically drains the flexible hose and shower head (ref. 880).
Shower kit ideal for healthcare facilities, nursing homes, hospitals and clinics.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- HW flow rate reduced if CW fails
- Pressure-balancing: constant temperature
- Ergonomic: sculptured lever is easy to grip
- Water saving: flow rate regulated at 9 lpm

TECHNICAL CHARACTERISTICS

Auto-draining shower kit with EP mechanical mixer - Ref. 2539EPSHYG

Connector	M1/2"
Technology	SECURITHERM EP
Width	175mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass
Norms	ACS, BELGAQUA
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY