

# BINOPTIC MIX electronic mixer

Ref. 398MCHLH15

Mains supply, Ø 15mm compression fittings

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 398MCHLH15**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexibles with filters and solenoid valve Ø 15mm compression fittings.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Drop height: 250mm for countertop washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 398MCHLH15**

|              |                                                                                                                                                                         |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply       | Secteur 230/12 V                                                                                                                                                        |
| Connector    | M1/2" Ø 15                                                                                                                                                              |
| Technology   | Electronic                                                                                                                                                              |
| Drop height  | 250mm                                                                                                                                                                   |
| Spout length | 185mm                                                                                                                                                                   |
| Flow rate    | 3 lpm                                                                                                                                                                   |
| Norms        |   |
| Warranty     |                                                                                      |



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial duty flush



LED diagnostic aid

