

# BINOPTIC MIX electronic mixer

Ref. 488MCHLH15

Battery-operated, Ø 15mm compression fittings

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 488MCHLH15**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexibles with filters and solenoid valve Ø 15mm compression fittings.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Drop height: 170mm for semi-recessed washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 488MCHLH15**

|               |                                                                                     |
|---------------|-------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                        |
| Connector     | M1/2" Ø 15                                                                          |
| Technology    | Electronic                                                                          |
| Drop height   | 170mm                                                                               |
| Spout length  | 175mm                                                                               |
| Flow rate     | 3 lpm                                                                               |
| Norms         |  |
| Warranty      |  |
| Repairability |  |



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial duty flush



LED diagnostic aid

