

## BINOPTIC electronic tap

Ref. 48801515

Battery-operated, Ø 15mm compression fittings

### DESCRIPTION

**BINOPTIC electronic tap - Ref. 48801515**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexible with filter and solenoid valve Ø 15mm.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Drop height: 170mm for semi-recessed washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 48801515**

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| Supply       | 6V battery                                                                          |
| Connector    | M1/2" Ø 15                                                                          |
| Technology   | Electronic                                                                          |
| Drop height  | 170mm                                                                               |
| Spout length | 175mm                                                                               |
| Flow rate    | 3 lpm                                                                               |
| Norms        |  |
| Warranty     |  |



### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Duty flush limits bacterial proliferation
-  LED diagnostic aid

