

Mechanical basin mixer

Ref. 2445

Wall-mounted mixer with swivel spout L .200mm, sculptured lever









DESCRIPTION

Mechanical basin mixer - Ref. 2445





Wall-mounted mechanical basin mixer.
 Mechanical mixer with flat, swivelling under spout L. 200mm with hygienic flow straightener.
 Spout suitable for fitting a BIOFIL point-of-use filter.
 Securitouch thermal insulation prevents burns.
 Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume.
 Flow rate 5 lpm 3 bar.
 Chrome-plated brass body.
 Sculptured control lever.
 Mixer with 150mm centres, supplied with offset STOP/CHECK wall connectors M1/2" M3/4" ideal for hospitals.
 Recommended installation height: 110 - 200mm above the basin surface.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Mixer suitable for people with reduced mobility.
 Wall-mounted mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2445

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated
Norms	   
Warranty	
Repairability	

ADVANTAGES

-  Hygiene: smooth interior reduces bacteria
-  Pre-set maximum temperature limiter
-  Securitouch thermal insulation prevents burns
-  Ergonomic sculptured control lever is easy to grip

