

Mechanical basin mixer

Ref. 2445

Wall-mounted mixer with swivel spout L .200mm, sculptured lever



DESCRIPTION

Mechanical basin mixer - Ref. 2445

Wall-mounted mechanical basin mixer.
 Flat, swivelling under spout L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.
 Securitouch thermal insulation prevents burns.
 Ø 40mm ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume (reduces bacterial niches).
 Flow rate 5 lpm 3 bar.
 Chrome-plated brass body.
 Sculptured control lever.
 Supplied with STOP/CHECK connectors M1/2" M3/4" ideal for hospitals.
 Recommended installation height: 110 - 200mm above the basin surface.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Mixer suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2445

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Finish	Chrome-plated
Norms	ACS WRAS Blue Mark NSF
Warranty	30 YEARS WARRANTY
Repairability	50 YEARS REPAIRABILITY

ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Ergonomic sculptured control lever is easy to grip

