

SECURITHERM EP pressure-balancing basin mixer

Ref. 2445EPS

Wall-mounted mixer with swivel spout L .200mm, sculptured lever



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2445EPS

Wall-mounted SECURITHERM pressure-balancing basin mixer. Mechanical mixer with flat swivelling under spout L. 200mm with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Anti-scalding safety: HW flow is reduced if CW fails (and vice versa).

Mixer with Securitouch thermal insulation prevents burns.

Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Sculptured control lever.

Mixer with 150mm centres supplied with offset standard connectors M1/2" M3/4".

Filters and non-return valves.

Recommended installation height: 110 - 200mm above the basin surface.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.







Mixer suitable for people with reduced mobility.

Wall-mounted mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2445EPS

Connector	M1/2"
Technology	SECURITHERM EP mixer, Securitouch
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated

Norms	   
Warranty	
Repairability	

ADVANTAGES



EP: HW flow reduced if CW fails



Securitouch thermal insulation prevents burns



EP: reduces pressure variations



Hygiene: smooth interior reduces bacteria

