Mechanical basin mixer

Ref. 2445L

Wall-mounted mixer with swivel spout L .200mm, Hygiene lever L. 150mm



DESCRIPTION

Mechanical basin mixer - Ref. 2445L

Wall-mounted mechanical basin mixer.

Mechanical mixerwith flat, swivelling under spout L. 200mm with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Mixer with Securitouch thermal insulation prevents burns.

Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm requires no manual contact..

Mixer with 150mm centres supplied with offset STOP/CHECK connectors M1/2" M3/4" ideal for hospitals.

Recommended installation height: 110 - 200mm above the basin surface.

Mechanical mixer ideal for healthcare facilities, retirement and care homes. hospitals and clinics.

Mixer suitable for people with reduced mobility.

Wall-mounted mixer with 30-year warranty.

ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Hygiene control lever requires no manual contact

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2445L

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated
Norms	ACS WRAS OVER DECEMBER 1
Warranty	30 gg wasanty
Repairability	50° SEPARABILITY



