Mechanical basin mixer

Ref. 2445L

Wall-mounted mixer with swivel spout L .200mm, Hygiene lever L. 150mm



DESCRIPTION

Mechanical basin mixer - Ref. 2445L

Wall-mounted mechanical basin mixer.

Flat, swivelling under spout L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Securitouch thermal insulation prevents burns.

Ø 40mm ceramic cartridge with pre-set maximum temperature limiter. Body and spout with smooth interiors and low water volume (reduces bacterial niches).

Flow rate 5 lpm at 3 bar.

Chrome-plated brass body.

Hygiene control lever L. 150mm.

Supplied with STOP/CHECK connectors M1/2" M3/4" ideal for hospitals.

Mixer suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2445L

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Finish	Chrome-plated
Norms	ACS WRAS 🎡 🗓
Norms Warranty	ACS SWRAS () () () () () () () () () (

ADVANTAGES



Hygiene: smooth interior reduces bacteria




Pre-set maximum temperature limiter




Securitouch thermal insulation prevents burns



Hygiene control lever requires no manual contact





© DELABIE https://www.delabie.com