

# SECURITHERM EP pressure-balancing basin mixer

Ref. 2445LEP

Wall-mounted mixer with swivel spout L. 200mm, Hygiene lever L. 150mm



## DESCRIPTION

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2445LEP**

Wall-mounted SECURITHERM pressure-balancing basin mixer. Wall-mounted mixer with flat swivelling under spout L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

Anti-scalding safety: HW flow rate is reduced if CW fails (and vice versa). Stable temperature regardless of flow rate and pressure variations in the system.

Securitouch thermal insulation prevents burns.

Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduces bacterial niches).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm.

Mixer supplied with offset STOP/CHECK wall connectors M1/2" M3/4" ideal for hospitals.

Recommended installation height: 110 - 200mm above the basin surface.







Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2445LEP**

Connector	M1/2"
Technology	SECURITHERM EP mixer, Securitouch
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated
Norms	ACS    
Warranty	
Repairability	

## ADVANTAGES



EP: HW flow reduced if CW fails



Securitouch thermal insulation prevents burns



EP: reduces pressure variations



Hygiene: smooth interior reduces bacteria

