Mechanical basin mixer

Ref. 2445LS

Wall-mounted mixer with swivel spout L .200mm, Hygiene lever L. 150mm



DESCRIPTION

Mechanical basin mixer - Ref. 2445LS

Wall-mounted mechanical basin mixer.

Mechanical mixer with flat, swivelling under spout L. 200mm with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Mixer with Securitouch thermal insulation prevents burns.

Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm requires no manual contact.

Mixer with 150mm centres supplied with standard connectors M1/2" M3/4".

Recommended installation height: 110 - 200mm above the basin surface.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Wall-mounted mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2445LS

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated
Norms	ACS OWRAS OF THE PROPERTY OF T
Warranty	30 S

ADVANTAGES



Hygiene: smooth interiors reduce bacteria




Pre-set maximum temperature limiter




Securitouch thermal insulation prevents burns



Hygiene control lever requires no manual contact





https://www.delabie.com

© DELABIE