

# Mechanical basin mixer

Ref. 2445LS

Wall-mounted mixer with swivel spout L. 200mm, Hygiene lever L. 150mm



## DESCRIPTION

**Mechanical basin mixer - Ref. 2445LS**

Wall-mounted mechanical basin mixer.  
 Flat, swivelling under spout L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.  
 Securitouch thermal insulation prevents burns.  
 Ø 40mm ceramic cartridge with pre-set maximum temperature limiter.  
 Body and spout with smooth interiors and low water volume (reduces bacterial niches).  
 Flow rate 5 lpm at 3 bar.  
 Chrome-plated brass body.  
 Hygiene control lever L. 150mm.  
 Supplied with standard connectors M1/2" M3/4".  
 Recommended installation height: 110 - 200mm above the basin surface.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer suitable for people with reduced mobility.  
 30-year warranty.

## ADVANTAGES



Hygiene: smooth interiors reduce bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Hygiene control lever requires no manual contact

## TECHNICAL CHARACTERISTICS

**Mechanical basin mixer - Ref. 2445LS**

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Finish	Chrome-plated
Norms	ACS WRAS
Warranty	30 YEARS WARRANTY
Repairability	50 YEARS REPAIRABILITY

