

# Mechanical basin mixer

Ref. 2445S

Wall-mounted mixer with swivel spout L .200mm, sculptured lever



## DESCRIPTION

**Mechanical basin mixer - Ref. 2445S**

Wall-mounted mechanical basin mixer.  
 Mechanical mixer with flat, swivelling under spout L. 200mm with hygienic flow straightener.  
 Spout suitable for fitting a BIOFIL point-of-use filter.  
 Mixer with Securitouch thermal insulation prevents burns.  
 Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.  
 Body and spout with smooth interiors and low water volume.  
 Flow rate regulated at 5 lpm.  
 Chrome-plated brass body.  
 Sculptured control lever.  
 Mixer with 150mm centres supplied with offset standard connectors M1/2" M3/4".  
 Recommended installation height: 110 - 200mm above the top of the basin.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer suitable for people with reduced mobility.  
 Wall-mounted mechanical mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Mechanical basin mixer - Ref. 2445S**

|                     |                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector           | M1/2"                                                                                                                                                                                                                                                                                                                                           |
| Technology          | Securitouch                                                                                                                                                                                                                                                                                                                                     |
| Spout length        | 200mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate           | 5 lpm                                                                                                                                                                                                                                                                                                                                           |
| Temperature limiter | YES                                                                                                                                                                                                                                                                                                                                             |
| Finish              | Chrome-plated                                                                                                                                                                                                                                                                                                                                   |
| Norms               |     |
| Warranty            |                                                                                                                                                                                                                                                              |
| Repairability       |                                                                                                                                                                                                                                                              |

## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Ergonomic sculptured control lever is easy to grip

