

Mechanical basin mixer

Ref. 2445S

Wall-mounted mixer with swivel spout L .200mm, sculptured lever



DESCRIPTION

Mechanical basin mixer - Ref. 2445S

Wall-mounted mechanical basin mixer.
 Flat, swivelling under spout L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
 Securitouch thermal insulation prevents burns.
 Ø 40mm ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume (reduces bacterial development).
 The water velocity in these tubes significantly reduces the development of the biofilm.
 Flow rate regulated at 5 lpm.
 Chrome-plated brass body.
 Sculptured control lever.
 Supplied with offset standard connectors M1/2" M3/4".
 Recommended installation height: 110 - 200mm above the top of the basin.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Mixer suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Securitouch thermal insulation prevents burns



Ergonomic sculptured control lever is easy to grip

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2445S

Connector	M1/2"
Technology	Securitouch
Spout length	200mm
Flow rate	5 lpm
Finish	Chrome-plated
Norms	ACS WWRAS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

