

# TEMPOMATIC 4 electronic tap

Ref. 443416

Integrated batteries



## DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443416

Wall-mounted electronic basin tap:  
Lithium 123 6V batteries integrated.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated stainless steel body, L. 130mm.  
Cap fixed in place by 2 concealed screws.  
Stopcock.  
For cross wall installation.  
Anti-blocking security.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443416

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Connector     | M1/2"                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Technology    | Electronic                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Spout length  | 130mm                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Norms         |    <br> |
| Warranty      |                                                                                                                                                                                                                                                                                                                                                     |
| Repairability |                                                                                                                                                                                                                                                                                                                                                     |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing tap

