TEMPOMATIC 4 electronic tap

Ref. 443416

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443416

Wall-mounted electronic basin tap:

Lithium 123 6V batteries integrated.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body, L. 130mm.

Cap fixed in place by 2 concealed screws.

Stopcock.

For cross wall installation.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443416

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	130mm
Flow rate	3 lpm
Norms	ACS W
Warranty	30 g

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing tan

