

PREMIX NANO thermostatic mixing valve

Ref. 732230

For mixed water from 34 - 60°C



DESCRIPTION

PREMIX NANO thermostatic mixing valve - Ref. 732230

Thermostatic mixing valve for mixed water distribution from 34 - 60°C:
 For 1 to 2 taps or 1 shower.
 Anti-scalding safety: automatic water shut-off in case of cold water supply failure.
 Cold shower failsafe: automatic shut-off in case of hot water supply failure.
 Temperature pre-set at 38°C, can be adjusted by the installer from 34 - 60°C.
 Non-return valves and filters.
 Recommended flow rate range: 3 - 12 lpm.
 Thermal shocks are possible.
 Polished chrome body, hot water inlet F3/8", cold water inlet M3/8" and mixed water outlet M3/8".
 Supplied with 3/8" connection kit.
 30-year warranty.

TECHNICAL CHARACTERISTICS

PREMIX NANO thermostatic mixing valve - Ref. 732230

Connector	3/8"
Technology	Thermostatic
Height	70mm
Finish	Chrome-plated
Norms	  
Warranty	
Repairability	

ADVANTAGES



Automatic shut-off if hot or cold water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

