

# TEMPOMATIC 4 urinal valve

Ref. 479410

Electronic with integrated batteries

## DESCRIPTION

TEMPOMATIC 4 urinal valve - Ref. 479410

Exposed electronic urinal valve with integrated batteries:  
 Battery-operated with integrated CR 123 3V Lithium batteries.  
 For wall-mounted, exposed installation.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the valve body.  
 Shockproof infrared presence detection sensor.  
 Detection delay is 10 sec.  
 3 programmes (rinsing volume adjustable in accordance to the type of urinal).  
 High-frequency mode (exclusive to DELABIE):  
 - short rinse after each user  
 - complementary rinse after busy period.  
 Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.  
 Compatible with rain water.  
 Flow rate 0.15 L/sec. at 3 bar, can be adjusted.  
 Integrated stopcock and flow rate adjuster.  
 One-piece chrome-plated metal body.  
 M $\frac{1}{2}$ " connection.  
 Straight for in-line supply, outlet M $\frac{1}{2}$ " 35mm gap from wall.  
 Suitable for people with reduced mobility.  
 30-year warranty.

Ideal for replacing old installations:  
 Can easily be installed where there was previously a time flow urinal.

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 urinal valve - Ref. 479410

|            |                                                                                     |
|------------|-------------------------------------------------------------------------------------|
| Supply     | 6V batteries                                                                        |
| Connector  | M $\frac{1}{2}$ "                                                                   |
| Technology | Electronic                                                                          |
| Height     | 155mm                                                                               |
| Depth      | 85mm                                                                                |
| Flow rate  | 0.15 l/sec                                                                          |
| Warranty   |  |



## ADVANTAGES



Total hygiene: no manual contact



High-frequency mode



Batteries integrated into the valve body



Hygienic duty flush

