

## TEMPOMATIC 4 urinal valve

Ref. 479412

Electronic with integrated batteries



### DESCRIPTION


TEMPOMATIC 4 urinal valve - Ref. 479412

Exposed electronic urinal valve with integrated batteries:  
 Battery-operated with integrated CR 123 6V Lithium batteries.  
 For wall-mounted, exposed installation.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the valve body.  
 Shockproof infrared presence detection sensor.  
 Detection delay is 10 sec.  
 3 programmes (rinsing volume adjustable in accordance to the type of urinal).  
 High-frequency mode (exclusive to DELABIE):  
 - short rinse after each user  
 - complementary rinse after busy period.  
 Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.  
 Compatible with rain water.  
 Flow rate 0.15 L/sec. at 3 bar, can be adjusted.  
 Integrated stopcock and flow rate adjuster.  
 One-piece chrome-plated metal body.  
 M1/2" connection.  
 Angled for recessed supply with Ø 35mm neck tube.  
 For standard urinals: 50mm gap from wall.  
 Suitable for people with reduced mobility.  
 30-year warranty.





Ideal for replacing old installations:  
 Can easily be installed where there was previously a time flow urinal.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 urinal valve - Ref. 479412

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Height	450mm
Depth	85mm
Flow rate	0.15 l/sec.
Width to the wall	50mm
Warranty	

### ADVANTAGES

-  Total hygiene: no manual contact
-  High-frequency mode
-  Batteries integrated into the valve body
-  Hygienic duty flush

