SECURITHERM EP pressure-balancing basin mixer

Ref. 2564T1EP

Tall single hole, single control mixer with EP cartridge



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2564T1EP

Deck-mounted basin mixer with SECURITHERM pressure-balancing.
Single hole, single control mixer with swivelling spout H. 165mm L. 140mm.
Tall mixer with BIOSAFE hygienic outlet suitable for fitting a BIOFIL point-of-use filter.
Anti-scalding safety: HW flow reduces if CW supply fails (and vice versa).
Stable temperature regardless of pressure and flow rate variations in the system.
Ø 35mm ceramic cartridge with pressure balancing and pre-set maximum temperature limiter.
Body and spout with smooth interiors (reduces bacterial development).
Thermal shocks are possible without removing the control lever or shutting off the cold water.
Flow rate regulated at 5 lpm.
Chrome-plated brass body and base.
Hygiene control lever L. 185mm requires no manual contact.
PEX flexibles F3/8" with filters and non-return valves.
Fixings reinforced via 2 stainless steel rods.
Mechanical mixer with pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.


ADVANTAGES

- EP: HW flow reduces if CW supply fails
- EP: reduces pressure variations
- Thermal shocks are possible without removing lever
- Hygiene: smooth interior reduces bacteria

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2564T1EP

Connector	F3/8"
Technology	SECURITHERM EP
Height	322mm
Drop height	165mm
Spout length	140mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS WRAS



Warranty	
Repairability	