

TEMPOMATIC urinal valve

Ref. 428206

Electronic, battery-operated




DESCRIPTION

TEMPOMATIC urinal valve - Ref. 428206





Cross wall electronic urinal valve:
 CR123 6V lithium battery-operated, electronic control unit with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".
 Cross wall installation \leq 225 mm.
 Shock-resistant infrared presence detection sensor.
 Detection distance, time flow and flow rate can be adjusted during installation.
 Detection delay is 3 seconds.
 Automatic pre-rinse is possible.
 Time flow ~3 seconds, can be adjusted from 3 - 12 seconds.
 Hygienic duty flush every 24 hours after last use: prevents vacuums.
 Flow rate 0.3 L/sec. at 3 bar, can be adjusted.
 Wall plate flush to the wall.
 Threaded rod can be cut to size.
 Compatible with rain water.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428206

Supply	6V batteries
Connector	1/2"
Technology	Electronic
Length	225mm
Flow rate	0,3 l/sec
Warranty	

ADVANTAGES

-  Total hygiene: no manual contact
-  ECO time flow 3 seconds
-  Cross wall installation
-  Hygienic duty flush

