SECURITHERM thermostatic shower mixer

Ref. 9741

Dual control thermostatic shower mixer



DESCRIPTION

SECURITHERM thermostatic shower mixer - Ref. 9741

SECURITHERM dual control thermostatic shower mixer:
Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold water showers if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic cartridge to adjust the temperature.
¼-turn ceramic head for flow rate adjustment.
Temperature control from 25 - 41°C.
Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.
Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and ERGO control knobs.
M1/2" shower outlet.
Mixer with no connectors with integrated filters and non-return valves on the F3/4" inlets.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- SECURITHERM: Optimum anti-scalding safety
- Double maximum temperature limiter
- Securitouch thermal insulation prevents burns
- Mixer specifically for refurbishment

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic shower mixer - Ref. 9741

Connector	F3/4"
Technology	SECURITHERM dual control thermostatic mixer, Securitouch
Length	286mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 YEAR WARRANTY



