

SECURITHERM Securitouch thermostatic shower mixer

Ref. 9769

Thermostatic mixer with no non-return valves



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. 9769

SECURITHERM dual control thermostatic shower mixer.
Thermostatic mixer with no non-return valves on the inlets (reduces bacterial proliferation).

No risk of cross flow between the hot and cold water.

Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge to adjust the temperature.

1/4-turn ceramic head for flow rate adjustment.

Temperature control up to 43°C.

Double temperature limiter: first limiter set at 41°C can be overridden, second limiter set at 43°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate limited to 9 lpm at 3 bar.

ERGO control knobs.

M1/2" shower outlet.

F3/4" inlets with integrated filters.

Mixer with no wall connectors.




Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. 9769

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer, no non-return valves
Length	260mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS  
Warranty	

ADVANTAGES



SECURITHERM: Optimum anti-scalding safety




Maximum hygiene: no non-return valves



Securitouch thermal insulation prevents burns



Mixer specifically for refurbishment



Repairability

