

SPORTING 2 SECURITHERM

electronic shower panel

Ref. 714906

Battery-operated, thermostatic, rain-effect spray



DESCRIPTION

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714906

Thermostatic electronic shower panel - top inlets:
 Anodised aluminium and chrome-plated satin finish panel.
 Slimline structure with concealed fixings.
 Battery-operated with CR123 6V Lithium batteries.
 Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm).
 Shuts off voluntarily or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate 6 lpm at 3 bar, rain effect spray.
 Tamperproof fixed shower head with automatic flow rate regulation.
 Accessible filters and non-return valves.
 Integrated stopcocks.
 M½" connections for top inlets.
 Electronic shower panel suitable for people with reduced mobility.
 30-year warranty.
 SECURITHERM technology:
 Thermostatic shower mixer directly integrated in the head of the shower panel.
 Temperature set by the installer.
 Stable temperature, pre-set at 38°C.
 Anti-scalding failsafe: automatic shut-off if the cold water fails.
 Anti-cold showers function: automatic shut-off if the hot water fails.

ADVANTAGES



Exceptional water savings: 80%



Anti-bacterial proliferation duty flush



Immediate shut-off if cold water fails




Streamlined design, concealed fixings

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714906

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Height	1020mm
Depth	21mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium



Norms

ACS



CE

Warranty

