DELABIE

SPORTING 2 SECURITHERM electronic shower panel

Ref. 714906

Battery-operated, thermostatic, rain-effect spray

DESCRIPTION

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714906

Thermostatic electronic shower panel - top inlets: Anodised aluminium and chrome-plated satin finish panel. Extra flat structure with concealed fixings. Battery-operated with CR123 6V Lithium batteries. Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm). Shuts off voluntarily or automatically after ~60 seconds. Duty flush (~60 seconds every 24 hours after the last use). Flow rate 6 lpm at 3 bar, rain effect spray. Tamperproof fixed shower head with automatic flow rate regulation. Accessible filters and non-return valves. Integrated stopcocks. M¹/₂" connections for top inlets. Electronic shower panel suitable for people with reduced mobility. 30-year warranty. SECURITHERM technology: Thermostatic shower mixer directly integrated in the head of the shower panel. Temperature set by the installer. Stable temperature, pre-set at 38°C. Anti-scalding failsafe: automatic shut-off if the cold water fails.

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714906

Anti-cold showers function: automatic shut-off if the hot water fails.

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Height	1020mm
Depth	21mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS WIRAS 📜 🖪 CE
Warranty	30 g

ADVANTAGES



Exceptional water savings: 80%



Anti-bacterial proliferation duty flush



Immediate shut-off if cold water fails



Streamlined design, concealed fixings

