

# SECURITHERM shower panel

Ref. 792370

Thermostatic time flow



## DESCRIPTION

**SECURITHERM shower panel - Ref. 792370**

Thermostatic time flow shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
SECURITHERM thermostatic mixer.  
Adjustable temperature control from cold water up to 38°C; with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if the cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Handset with removable flexible via rapid push-fit STOP connector.  
~30-second time flow valve for control of sliding handset on chrome-plated rail.  
Flow rate 6 lpm at 3 bar.  
Concealed fixings.  
Filters and non-return valves.  
Suitable for people with reduced mobility.  
30-year warranty.





## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792370**

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS 
Warranty	



## ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off iff cold water fails
-  80% water savings
-  Aluminium frame, brass controls

