

# OUTDOOR time flow shower column

Ref. 717521

Time flow, 2 showers and 1 foot-rinse

## DESCRIPTION

**OUTDOOR time flow shower column - Ref. 717521**

Time flow shower column:

Anodised aluminium shower column ready to fit.

Fitted with two showers and one foot-rinse.

Bottom inlet via stopcock F $\frac{3}{4}$ ".

TEMPOSOF 2 time flow valves for mixed water supply.

Soft-touch operation.

Time flow ~15 seconds for shower and ~3 seconds for foot-rinse.

Chrome-plated, tamperproof, scale-resistant ROUND shower heads with automatic flow rate regulation at 6 lpm at 3 bar.

Stainless steel foot-rinse with flow rate 3 lpm at 3 bar.

Filters.

Access panel with isolation valve and purge.

Can easily be protected or taken apart in winter.

Suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

**OUTDOOR time flow shower column - Ref. 717521**

|            |                                                                                                                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector  | F $\frac{3}{4}$ "                                                                                                                                                                                                                                           |
| Technology | Time flow                                                                                                                                                                                                                                                   |
| Height     | 2,245mm                                                                                                                                                                                                                                                     |
| Flow rate  | Shower 6 lpm, Foot-rinse 3 lpm                                                                                                                                                                                                                              |
| Finish     | Aluminium                                                                                                                                                                                                                                                   |
| Norms      |    |
| Warranty   |                                                                                                                                                                          |



## ADVANTAGES



80% water savings



Soft-touch operation



Anti-corrosion anodised aluminium



Supplied ready to fit

