

Mechanical mixer for sinks or troughs

Ref. 2510

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm



DESCRIPTION

Mechanical mixer for sinks or troughs - Ref. 2510

Deck-mounted mechanical sink mixer.

Single hole mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interiors.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Body and spout made from chrome-plated brass.

Flow limited to 9 lpm at 3 bar.

Sculptured control lever.

Supplied with PEX flexibles F3/8".

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2510

Connector	F3/8"
Height	178mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	
Repairability	

