SECURITHERM EP pressure-balancing mixer

Ref. 2721TEP

Single hole mechanical mixer H. 95mm L. 120mm



DESCRIPTION

SECURITHERM EP pressure-balancing mixer - Ref. 2721TEP

Deck-mounted mechanical basin mixer with pressure-balancing.
Single hole mixer with a curved spout H. 95mm L. 120mm fitted with a hygienic BIOSAFE outlet.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
Stable temperature regardless of variations in pressure and flow rate in the system.
Body and spout with smooth interiors (reduced bacterial development).
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Flow rate regulated at 5 lpm at 3 bar.
Solid control lever.
No pop-up waste.
F3/8" PEX flexibles with filters and non-return valves.
Reinforced fixing via 2 stainless steel rods.
Mechanical mixer with SECURITHERM pressure-balancing, ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.


ADVANTAGES

- HW flow rate reduced if CW supply fails
- EP: reduces temperature variations
- Hygiene: smooth interior reduces bacteria
- Thermal shock without removing the control lever

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing mixer - Ref. 2721TEP

Connector	F3/8"
Technology	SECURITHERM EP mechanical mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	



© DELABIE

Warranty	
Repairability	