SECURITHERM EP pressure-balancing basin mixer

Ref. 2521TEP

Single hole mechanical mixer H. 85mm, L. 135mm



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521TEP

Deck-mounted mechanical basin mixer with pressure-balancing.
Single hole mechanical mixer with spout H. 85mm L. 135mm with BIOSAFE hygienic spout outlet.
Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
Anti-scalding safety: HW flow rate is reduced if cold water supply fails (and vice versa).
Stable temperature regardless of pressure and flow rate in the system.
Flow rate limited to 5 lpm at 3 bar.
Solid control lever.
Without pop-up waste.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- HW flow rate reduced if CW fails
- EP: reduces temperature variations
- Hygienic: BIOSAFE hygienic outlet with no grid
- Ergonomic: solid control lever is easy to grip

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521TEP

Connector	F3/8"
Technology	SECURITHERM EP mechanical mixer
Height	165mm
Drop height	85mm
Spout length	135mm
Flow rate	5 lpm at 3 bar
Finish	Chrome-plated brass
Norms	ACS, BELGAQUA, DVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

